



RFID Tags
That Work
On Anything!

ORION "Mini"

The Orion "Mini" tag has been engineered and developed to be the lowest cost metal mount tag on the market without sacrificing read range or performance. The Orion "Mini" has applications for asset tracking, item level retail, and many uses on metal and other hard-to-read surfaces.



Chip	<p><u>Higgs 3</u></p> <ul style="list-style-type: none"> • Meets EPCglobal™ Gen2 (V 1.2.0) as well as ISO/IEC 18000-6C • 800 Bits of Nonvolatile Memory • 96-EPC Bits, extensible to 496 Bits • 512 User Bits • 64 Bit Unique TID • 32 Bit Access and Kill Passwords • Pre-Programmed with a unique, unalterable 64-Bit Serial Number • User Memory can be Block Perma-Locked as well as read password protected in 64 Bit Blocks • Supports all Mandatory and Optional Commands including Item Level Commands
Inlay	• Copper etched
Size	• 1" x 4" finished size
Construction	• 2 lb Closed Cell HDPE foam .125" thickness with a .002" conformable face sheet
Read Range	• 15 to 20 feet
Frequency	• 902-928 megahertz
Adhesion	• Pressure sensitive permanent adhesive
Application	• Minimum application temperature 50F service range -10F to 140F
<p>.002" Conformable Material Laminating Adhesive RFID Inlay Laminating Adhesive .125" HDPE Foam Mounting Pressure Sensitive Adhesive Release Liner</p>	



10601 NW Ambassador Drive Suite H
Kansas City, MO 64153

DIRECT LINE: 1-816-891-9944
www.starporttech.com